



INCOMAC s.r.l.  
Via Ferraris, 50 - P.O. Box 80  
31044 MONTEBELLUNA (TREVISO) ITALIA  
Tel. (0423) 21646 r.a. - Fax (0423) 301633  
Indirizzo E-mail : [incomac@incomac.it](mailto:incomac@incomac.it)  
Internet : <http://www.incomac.com>

### QUOTE REQUEST QUESTIONNAIRE

COMPANY NAME \_\_\_\_\_

ADDRESS : \_\_\_\_\_

PHONE : \_\_\_\_\_ FAX. \_\_\_\_\_

PRODUCTION ACTIVITY : \_\_\_\_\_

REQUIRED DRIER TYPE :  CONVENTIONAL  CONDENSATION (by electricity)

DRYING UNIT PROVIDED WITH PREFABRICATED DRYING CHAMBER

COMPONENTS ONLY AND DOORS (for masonry chamber built on Incomac project or for existing chamber)

AVAILABLE ENERGY SOURCE :  ELECTRICITY  WOOD WASTE

GAS  GAS OIL

EXISTING BOILER :  YES  NO

AVAILABLE THERMAL CAPACITY FOR THE KILNS : \_\_\_\_\_ Kcal/h

BOILER PRODUCTION :  HOT WATER  OVERHEATED WATER

STEAM

REQUIRED DRYING CAPACITY PER CYCLE : \_\_\_\_\_ m<sup>3</sup>/cycle

REQUIRED DRYING CAPACITY PER YEAR : \_\_\_\_\_ m<sup>3</sup>/vaer

TIMBER SPECIES TO BE DRIED :  HARDWOOD type: \_\_\_\_\_

SOFTWOOD type: \_\_\_\_\_

OTHERS type: \_\_\_\_\_

INITIAL MOISTURE CONTENT : \_\_\_\_\_ % FINAL MOISTURE CONTENT : \_\_\_\_\_ %

STANDARD STACK DIMENSIONS : \_\_\_\_\_ x \_\_\_\_\_ mm.

MAX. LENGHT OF THE STACK-PLANK : \_\_\_\_\_ mm.

AVERAGE THICKNESS OF THE PLANK : \_\_\_\_\_ mm.

AVERAGE THICKNESS OF THE LEDGE : \_\_\_\_\_ mm.

REQUIRED LOADING TYPE :  FORK-LIFT  TROLLEYS AND RAILS

ELECTRONIC DEVICES :  AUTOMATIC MICROPROCESSOR

CONTROL SYSTEM BY COMPUTER

FURTHER INFORMATION : \_\_\_\_\_

---

---

---